TOSHIBA

For all your data storage needs...

SD-M1712 HH DVD-ROM

Features Include: ATAPI Interface. 192kB Buffer

Memory. 100,000 Hours MTBF.

Retail Kit Include: IDE DVD-ROM Drive. Multilingual Installation Guide. All Cables, Screws and Leads. CD Pen. Manuals & More CD. InterVideo WinDVD, DVD Playback Software.



Toshiba Storage Device Division leads the market in the development, design and manufacturing of DVD-RAM, DVD-ROM, Combination drives and PC Card & mobile hard disk drives. SDD markets high-quality peripherals to original equipment manufacturers, value-added resellers, value-added dealers, system integrators and distributors in Europe. Inherent in the company's product line is high-quality engineering and manufacturing which has established Toshiba products as worldwide leaders.

Supported Disc Formats:
DVD-ROM, DVD-R, DVD-RW, DVD-RAM, CD-ROM,
CD-R, CD-RW, CD-DA, CD+(E)G, CD-MIDI, CD-TEXT,
CD-ROM XA, CD-I, CD-I Bridge
(PhotoCD, VideoCD),
Multisession CD (PhotoCD, CD-EXTRA, CD-R, CD-RW)

Interface: ATAPI/IDE

Random Seek Time:
DVD: 85ms
CD: 80ms
DVD-RAM: 130ms

Continuous Data Transfer Rate:
DVD-R/RW: (4.8x) 6,536KB/sec
DVD-ROM: (16x max) 21,6000KB/sec
DVD-RAM: (2x) 2,700KB/sec
CD-ROM: (48x max) 7,2000KB/sec
CD-DA: (32x) 4,800KB/sec

Buffer Capacity: 192kB

Power Consumption: 11W (DVD, Average) 12W (CD, Average)

MTBF: 100,000 hours Power Source: + 5V/+12V

Operating temperature 5-50°C (excluding media)

External dimensions (WxHxD) 146mm x 41.5mm x 193mm Weight 0.99kg

Storage Device Division, Hammfelddamm 8, 41460 Neuss, Germany Fax: +49 (0) 2131 158/473 Hotline: +49 (0) 1805 834373 Email: SDDinfo@toshiba-teg.com